



PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau


INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : H04L 12/64 // H04Q 7/22		(11) International Publication Number: WO 98/27698
A1		(43) International Publication Date: 25 June 1998 (25.06.98)
(21) International Application Number: PCT/FI97/00785		(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, GM, GW, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).
(22) International Filing Date: 15 December 1997 (15.12.97)		
(30) Priority Data: 965049 16 December 1996 (16.12.96) FI		
(71) Applicant (for all designated States except US): NOKIA TELECOMMUNICATIONS OY [FI/FI]; Keilalahdentie 4, FIN-02150 Espoo (FI).		
(72) Inventor; and (75) Inventor/Applicant (for US only): KARI, Hannu, H. [FI/FI]; Kullervonkuja 9 B 9, FIN-02880 Veikkola (FI).		
(74) Agent: KOLSTER OY AB; Iso Roobertinkatu 23, P.O. Box 148, FIN-00121 Helsinki (FI).		Published With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.

(54) Title: PACKET AND CIRCUIT SWITCHED COMMUNICATION IN A MOBILE COMMUNICATIONS NETWORK

(57) Abstract

An arrangement for establishing a packet switched and a circuit switched connection between a first telecommunications system (NSS) and a second telecommunications system (WAN) comprises: 1) a packet switched converter (PSDC) for establishing a packet switched connection towards the first telecommunications system (NSS) and 2) a circuit switched converter (CSDC) for establishing a circuit switched connection towards the first telecommunications system (NSS). According to the invention, the arrangement also comprises a common data communications controller (CDCC) for establishing a connection between said converters (PSDC, CSDC) and said second telecommunications system (WAN). The interface of the common controller (CDCC) towards the second telecommunications system (WAN) is independent of its interface towards the first telecommunications system (NSS). For eliminating overlapping functions it is advantageous for the common controller (CDCC) to be adapted to perform as many as possible of the functions performed by the arrangement.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GII	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakhstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

Packet and circuit switched communication in a mobile communications network

BACKGROUND OF THE INVENTION

The invention relates to an arrangement for implementing packet and
5 circuit switched communication in a mobile communications network.

Figure 1 shows the parts of a cellular mobile communications system which are relevant to the invention. Mobile stations MS communicate with base transceiver stations BTS over an air interface Um. The base transceiver stations are controlled by base station controllers BSC associated with mobile
10 services switching centres MSC. A subsystem administered by a base station controller BSC - including the base transceiver stations BTS controlled by it - is commonly called a base station subsystem BSS. The interface between a mobile services switching centre MSC and a base station subsystem BSS is called an A-interface. The part of the mobile communications system on the
15 MSC side of the A-interface is called a Network Subsystem NSS. Correspondingly, the interface between a base station controller BSC and a base transceiver station BTS is called an Abis-interface. A mobile services switching centre MSC switches incoming and outgoing calls. It performs similar functions as an exchange in a public switched telephone network PSTN. Additionally, it performs functions characteristic of mobile telecommunication
20 only, such as subscriber location administration, in co-operation with network subscriber registers (not separately shown in Figure 1).

A conventional radio connection used in digital mobile communications systems is circuit switched, i.e. radio resources allocated to a subscriber are reserved for the connection in question for the entire duration of
25 the call. GPRS (General Packet Radio Service) is a new service designed for digital mobile communications systems, such as the GSM system. Packet radio service is described in ETSI (European Telecommunication Standard Institute) recommendation TC-TR-GSM 01.60. By means of packet radio service, a mobile station MS user can be provided with a packet switched radio
30 connection which utilises radio resources in an efficient manner. In a packet switched connection, radio resources are reserved only when there is speech or data to be sent. Speech or data are assembled into packets with a predetermined length. When such a packet has been sent over the air interface Um, and the sending party does not immediately have a next packet to send, the
35 radio resource can be released to be used by other subscribers. This kind of

resource sharing is thus different from time division multiple access (TDMA), wherein the same physical channel is shared by several users in predetermined time slots.

Conventional cellular mobile communications systems, such as the
5 GSM system, or its derivative, DCS, support only circuit switched connections. As shown in Fig. 1, a packet switched connection can be implemented e.g. by connecting a specific terminal server to a direct data access (DDA) interface of an MSC.

Fig. 1 also shows a GPRS support node GSN, which controls the
10 operations of the packet radio service on the network side. The controlling comprises for example logging on and off the system by a mobile station (logon and logoff, respectively), routing area updating of a mobile station, and routing of data packets to the correct destination. A GSN node can be co-located with a base station controller BSC or a mobile switching centre MSC,
15 or it can be located apart from them. The interface between the GSN node and the base station controller BSC is called a Gb-interface.

An adapter, or a GSM-LAN interconnection unit (GLIU), is e.g. a terminal server, such as a router, having several V.24 serial interfaces towards the MSC for protocols like SLIP (Serial Line Interface Protocol) or PPP
20 (Point to Point Protocol), and a local area network (LAN) connection, such as Ethernet, towards the operator's LAN.

The GPRS support node GSN and the adapter GLIU comprise several similar parts, and they perform many similar functions. Both of them comprise an interface to the local area network, and their functions include substantially similar conversions between different protocols. Likewise, they both
25 perform different security checks and/or data compression and decompression.

In the arrangement according to Fig. 1, in the uplink direction the adapter GLIU converts, or adapts, a circuit switched data stream into data
30 packets, and in the downlink direction it converts data packets into a circuit switched data stream. Occasionally, functions independent of the communications mechanism, such as data decompression, decryption and/or packet routing, must be performed on the data packets. Control packets are handled locally in the particular node. In the downlink direction, the adapter GLIU performs
35 reverse operations, such as encryption and compression, etc.

The GPRS support node GSN performs functions almost similar to those performed by the adapter GLIU. However, instead of data arriving as

single characters, data arrive in packets. A packet can be a complete frame or a part thereof. On a packet switched connection, a resource is not reserved permanently. When a complete packet has been received, the process is substantially similar to the one performed by the GLIU.

- 5 On a circuit switched connection as well - i.e. via the GLIU - data propagate over the air interface Um in packets, but the sender sends each character separately. The mobile station comprises a protocol layer which assembles consecutive characters and sends them as packets. For the GSM system, it is irrelevant whether the characters to be sent in one go belong to
- 10 the same frame or not.

The primary purpose of a circuit switched and a packet switched network is to send data packets, such as TCP/IP packets, from a terminal equipment to a wide area network WAN. In a GSM/GPRS system, resource reservation in a circuit switched network is different from that in a packet

15 switched network.

Typically, the following functions are assigned to the GPRS support node GSN and the adapter GLIU:

Table 1:

- 20 1. packet assembly and disassembly
2. local handling of control packets
3. encryption and decryption
4. data compression and decompression
5. routing of packets
6. necessary security checks
- 25 7. access control
8. maintaining statistics
9. assembling billing data and transferring same to a billing system.

A problem in the prior art implementation described above is the increased system cost and complexity resulting from similar functions being

30 performed at two points of the system. Further, the prior art implementation is difficult to maintain, as changes have to be made in two different network elements simultaneously.

BRIEF SUMMARY OF THE INVENTION

It is an object of the invention to provide an arrangement that solves

35 the above problems relating to overlapping and complex network elements. The

object of the invention is achieved with systems comprising the characteristic features of the attached independent claims. The preferred embodiments of the invention are disclosed in the dependent claims.

The invention is based on the idea that the system comprises a common telecommunications controller via which data packets to be transmitted on circuit switched connections and packet switched connections are conveyed. A simpler construction is achieved by concentrating the overlapping functions in a common telecommunications controller. The cost of the system will also be lowered and its maintenance will be facilitated. A common telecommunications controller requires fewer software and hardware interfaces than two separate adapters do. It will be simpler to add new line and network protocols, because the additions bring about changes in a single network element only. Further, the inventive arrangement simplifies the demarcation of responsibilities between different network elements and their suppliers.

15 BRIEF DESCRIPTION OF THE DRAWINGS

The invention will now be described in more detail with reference to the preferred embodiments illustrated in the accompanying drawings, wherein:

Fig. 1 shows the parts of a mobile communications system which are relevant to the invention; and

20 Fig. 2 shows an arrangement according to the invention.

DETAILED DESCRIPTION OF THE INVENTION

Referring now to Fig. 2, a common (data) communications controller CDCC controls substantially all communications on circuit switched and packet switched connections. In an arrangement according to the invention, the controller CDCC performs most of the functions performed by the GPRS support node GSN and the adapter GLIU in the prior art solution shown in Fig. 1.

Functions 1 and 2 of Table 1 are specific to both circuit and packet switched traffic. Additionally, for example in the GSM system, function 3 has already been implemented on the connection between a mobile station MS and a base transceiver station BTS. Functions 4 to 9 of Table 1, on the other hand, can be performed by the common data communications controller CDCC.

In addition to the common data communications controller CDCC, only two simple protocol converters are needed. A circuit switched data con-

verter CSDC performs the necessary protocol conversions between the local area network LAN and the circuit switched network, the latter being shown in Fig. 2 as an MSC and an Interworking Function IWF. Correspondingly, a packet switched data converter PSDC performs the necessary protocol conversions between the local area network LAN and the packet switched network. In the implementation according to Fig. 2, a packet switched network is connected from the operator's local area network LAN directly to a base station controller BSC.

The functions of the converters PSDC and CSDC substantially consist of packet assembly and disassembly, and in the case of the PSDC, functions 2 and 3 of Table 1. The other functions mentioned in Table 1 can be concentrated in the common controller CDCC.

Thus, the arrangement for establishing a packet and circuit switched connection between a first telecommunications system NSS and a second telecommunications system WAN comprises: 1) a packet switched data converter PSDC for establishing a packet switched connection towards the first telecommunications system NSS and 2) a circuit switched data converter CSDC for establishing a circuit switched connection towards the first telecommunications system NSS. According to the invention, the arrangement also comprises a common data communications controller CDCC for establishing a connection between the converters PSDC, CSDC and the second telecommunications system WAN. The interface of the common communications controller CDCC towards the second telecommunications system WAN is independent of its interface towards the first telecommunications system NSS. This idea can also be expressed by stating that the converters PSDC and CSDC are independent of the second telecommunications system WAN. Only the common communications controller CDCC has to be able to interpret the protocols used in the WAN, which means that the controller CDCC is the only network element which must be upgraded if new network protocols and/or services are added.

For eliminating overlapping functions it is advantageous for the common communications controller CDCC to be adapted to perform as many as possible of the functions performed by the arrangement. It is especially advantageous to concentrate in the common communications controller CDCC most - preferably substantially all - functions which require logic going beyond simple protocol conversion. The functions requiring such logic include:

- data compression and decompression

- routing of packets
 - security checks
 - access control
 - maintaining statistics
- 5 - assembling billing data and transferring same to a billing system.

Fig. 2 shows, by way of example, the converters PSDC and CSDC connected to the common communications controller CDCC by the operator's local area network LAN. LAN technology is well understood, and complete hardware components and interface software are readily available in the field.

10 Alternatively, the common communications controller CDCC and the converters PSDC and CSDC can be integrated into one entity which performs substantially all the functions mentioned in Table 1. The parts CDCC, PSDC and CSDC of this entity are interconnected by means of a widely used or, alternatively, a proprietary parallel or serial interface. It is also conceivable to install

15 in the controller CDCC two different interfaces for the converters PSDC and CSDC.

Physically, the common communications controller CDCC can be implemented as a commercially available router, the software of which is adapted to each telecommunications system such that the router and its software can perform at least functions 4 to 9 of Table 1. The common communications controller CDCC can also be a general purpose or a customised computer including the necessary interfaces and software.

20

It will be obvious to a person skilled in the art that as the technology advances, the basic idea of the invention can be implemented in many different ways. The invention and its embodiments are therefore not limited to the examples described above, but they can be varied within the scope of the claims.

25

CLAIMS:

1. An arrangement for establishing a packet switched connection and a circuit switched connection between a first telecommunications system (NSS) and a second telecommunications system (WAN), said arrangement
5 comprising:
a packet switched converter (PSDC) for establishing a packet switched connection towards the first telecommunications system (NSS);
a circuit switched converter (CSDC) for establishing a circuit switched connection towards the first telecommunications system (NSS);
10 **characterized** in that:
said arrangement also comprises a common communications controller (CDCC) for establishing a connection between said converters (PSDC, CSDC) and said second telecommunications system (WAN), said common communications controller (CDCC) comprising a first and a second interface
15 towards said first and second telecommunications systems (NSS, WAN), respectively; and
the first interface of the common communications controller (CDCC) is independent of its second interface.
2. An arrangement according to claim 1, **characterized** in
20 that:
the packet switched converter (PSDC) and the circuit switched converter (CSDC) are substantially adapted only to convert the protocols used on said packet switched connection and said circuit switched connection, respectively, into a protocol which is used on a connection between the particular converter (PSDC, CSDC) and the common communications controller (CDCC); and
25 the common communications controller (CDCC) is adapted to perform substantially all the remaining functions to be performed in said arrangement.
3. An arrangement according to claim 1 or 2, **characterized**
30 in that said common communications controller (CDCC) is adapted to perform functions which are selected from a set including: data compression and decompression, routing of packets, security checks, access control, maintaining statistics, assembling billing data and transferring same to a billing system.

4. An arrangement according to claim 1, 2 or 3, **characterized** in that said common communications controller (CDCC) is connected to said packet switched converter (PSDC) and said circuit switched converter (CSDC) via a local area network (LAN).

5. An arrangement according to any one of claims 1 to 4, **characterized** in that said packet switched converter (PSDC) is operationally connected to a base station controller (BSC) of a mobile telecommunications system.

6. An arrangement according to any one of claims 1 to 5, **characterized** in that said circuit switched converter (CSDC) is operationally connected to a mobile switching centre (MSC) of a mobile telecommunications system.

7. A common communications controller (CDCC) for establishing connections between a first telecommunications system (NSS) and a second telecommunications system (WAN),

characterized in that said common communications controller (CDCC) comprises:

a first set of interface means to a circuit switched converter (CSDC) and to a packet switched converter (PSDC) for establishing a circuit switched and a packet switched connection, respectively, to said first telecommunications system (NSS);

a second set of interface means to said second telecommunications systems (WAN); wherein

said first set of interface means is independent of said second set of interface means.

Fig. 1





Fig. 2



INTERNATIONAL SEARCH REPORT

International application No.

PCT/FI 97/00785

A. CLASSIFICATION OF SUBJECT MATTER

IPC6: H04L 12/64 // H04Q 7/22

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC6: H04L, H04Q

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

WPIL, EDOC, JAPIO, INSPEC

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 5533019 A (JAY P. JAYAPALAN), 2 July 1996 (02.07.96), column 3, line 61 - column 4, line 61, figure 2 --	1-7
A	US 5533029 A (STEVEN H. GARDNER), 2 July 1996 (02.07.96), column 5, line 35 - column 7, line 25 --	1-7
A	WO 9508900 A1 (NOKIA TELECOMMUNICATIONS OY), 30 March 1995 (30.03.95), page 6, line 14 - page 7, line 11, figure 1 --	1-7

☒ Further documents are listed in the continuation of Box C.☒ See patent family annex.

* Special categories of cited documents:

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "B" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

18 May 1998

Date of mailing of the international search report

25 -05- 1998

Name and mailing address of the ISA/
Swedish Patent Office
Box 5055, S-102 42 STOCKHOLM
Facsimile No. +46 8 666 02 86

Authorized officer

Anders Ströbeck
Telephone No. +46 8 782 25 00

INTERNATIONAL SEARCH REPORT

International application No.

PCT/FI 97/00785

C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 5396539 A (ARNUNAS G. SLEKYS ET AL), 7 March 1995 (07.03.95), column 2, line 8 - column 3, line 40, figure 1 -----	1-7

INTERNATIONAL SEARCH REPORT
Information on patent family members

29/04/98

International application No.

PCT/FI 97/00785

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 5533019 A	02/07/96	CA 2156636 A	10/08/95
		FI 954571 A	27/09/95
		JP 8508870 T	17/09/96
		SE 9503360 A	30/11/95
		WO 9521492 A	10/08/95
US 5533029 A	02/07/96	AU 1094995 A	29/05/95
		US 5544222 A	06/08/96
		WO 9513685 A	18/05/95
WO 9508900 A1	30/03/95	AU 678534 B	29/05/97
		AU 7658694 A	10/04/95
		CN 1133666 A	16/10/96
		EP 0720806 A	10/07/96
		FI 98687 B,C	15/04/97
		FI 934115 A	21/03/95
		JP 9505951 T	10/06/97
US 5396539 A	07/03/95	US 5528664 A	18/06/96
		CA 2063901 A	26/09/92

This Page Blank (uspto)

This Page is Inserted by IFW Indexing and Scanning

Operational and is not part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☒ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.

This Page Blank (uspto)